



SM10G-SR

10Gb/s SFP+ Transceiver for Chelsio Adapters

Features

- Hot-pluggable SFP+ footprint
- Improved pluggable form factor
- Supports 9.95 to 10.5 Gb/s bit rates
- Maximum link length of 300m on 2000 MHz-Km MMF
- Uncooled 850nm VCSEL laser
- Receiver limiting electrical interface
- Duplex LC connector
- Built-in digital diagnostic functions

Applications

- 10GBASE-SR/SW 10G Ethernet
- 1200-Mx-SN-I 10G Fibre Channel

Specifications

- IEEE 802.3ae (10 GbE)
- SFF-8431
- SFF-8432

Regulatory Compliance

- Class 1 laser products
- US FDA regulatory compliant
- TÜV and CSA certified
- Meets the Class 1 safety requirements of EN (IEC) 60825 and 60950.

Physical and Environmental

- RoHS-6 compliant (lead-free)
- Commercial temperature range 0°C to 70°C
- Power dissipation < 1W
- Single 3.3V power supply

Compatible Adapters

- T520-CR
- T520-LL-CR
- T520-SO-CR
- T540-CR
- T520-OCP-SO
- T580-CR (QSA Mode)
- T580-LP-CR (QSA Mode)
- T580-SO-CR (QSA Mode)
- T580-OCP-SO (QSA Mode)

Overview

Chelsio's SM10G-SR 10Gb/s 850nm Multimode SFP+ optical transceivers are designed and certified for use with Chelsio's 10-Gigabit Ethernet Unified Wire Adapters.

The Chelsio SM10G-SR Transceiver is compatible with Chelsio's T5-based Unified Wire Adapters. The T5 adapters support PCI Express 3.0 host bus interface, and are optimized for storage, cloud computing, HPC, virtualization and other data center applications. The fifth-generation T5 ASIC technology from Chelsio provides the highest performance while dramatically lowering host-system CPU and memory overhead with on-board hardware that offloads TCP/IP, iSCSI, FCoE and iWARP RDMA processing. As a result, the system benefits from higher bandwidth, lower latency and reduced power consumption.



Transceiver Characteristics

Chelsio's SM10G-SR SFP+ transceivers are fully compliant with leading industry standards. They support the 2-wire serial communication protocol defined in the SFF-8472 and also conform to the EEPROM specifications defined in the GBIC standards with the same electrical specifications. Device details like transceiver capabilities, standard interfaces, manufacturer, etc. are provided by the standard SFP+ serial ID. Operating parameters such as transceiver temperature, laser bias current, transmitted optical power, received optical power and transceiver supply voltage are provided real-time by an enhanced digital diagnostic monitoring interface. Finally, a sophisticated alarm system warns users in case of anomalies in operating parameters.

The T5 Adapters with SM10G-SR SFP+ Transceiver enable a unified wire for LAN, SAN, and cluster traffic, built upon a combination of high bandwidth and low latency architecture along with a complete set of storage and cluster protocols operating over Ethernet (iSCSI, FCoE, and iWARP). Full Software suite was run with these modules and Chelsio recommends using these modules only with Adapters to allow the Adapter warranty and support structure to remain intact.

Ordering Information

Model: SM10G-SR

INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH CHELSIO PRODUCTS. NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. EXCEPT AS PROVIDED IN CHELSIO'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, CHELSIO ASSUMES NO LIABILITY WHATSOEVER, AND CHELSIO DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO SALE AND OR USE OF CHELSIO PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. CHELSIO PRODUCTS ARE NOT INTENDED FOR USE IN MEDICAL, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS. CHELSIO MAY MAKE CHANGES TO SPECIFICATIONS AND PRODUCT DESCRIPTIONS AT ANY TIME WITHOUT NOTICE.

Copyright © 2015 - Chelsio Communications - All Rights Reserved.