

AOC-SFP28-CABLE-10M

25 Gb/s 10m SFP28 to SFP28 Short Reach Active Optical Cable

Features

- Multiple conductor sizes for optimized performance
- Positive retention pull-release latch system
- High-density SFP28 connector
- Ultra-low crosstalk for enhanced performance
- Cost-effective and optimized for high-speed data center interconnects
- Programmable EEPROM for serial identification

Applications

- Ethernet 25G
- Rack-to-Rack, Shelf-to-Shelf Interconnect
- High Performance Networking, Storage, and clusters
- Hubs, switches, routers, servers

Specifications

- IEEE 802.3ae (10GbE)
- IEEE 802.3by (25GbE)

Regulatory Compliance

- SFF-8432

Physical and Environmental

- RoHS-6 compliant (lead-free)
- Operating temperature: 0°C to 70°C
- Single 3.3V power supply

Compatible Adapters

- T6225-CR
- T6225-LL-CR
- T6225-SO-CR
- T6225-OCP
- T6425-CR

Overview

Chelsio's AOC-SFP28-CABLE-10M 25Gb/s 10m SFP28 to SFP28 Short Reach Active Optical Cables are designed and certified for use with Chelsio's 25 Gigabit Ethernet Unified Wire Adapters. The Fiber Optics cables offer a cost-effective and power-efficient cabling solution for high-speed data applications.



The Chelsio AOC-SFP28-CABLE-10M Active optical cable is compatible with Chelsio's T6-based Unified Wire Adapters. The T6 adapters support PCI Express 3.0 host bus interface, and are optimized for storage, cloud computing, HPC, virtualization and other data center applications. The sixth-generation T6 ASIC technology from Chelsio provides the highest performance while dramatically lowering host-system CPU and memory overhead with on-board hardware that offloads TCP/IP, iSCSI, FCoE, iWARP RDMA, IPsec, TLS/SSL, DTLS and SMB 3.X crypto processing. As a result, the system benefits from higher bandwidth, lower latency and reduced power consumption.

Characteristics

Chelsio's AOC-SFP28-CABLE-10M SFP28 cables are fully compliant with IEEE 802.3by and IBTA specifications and adhere to RoHS-6 standards.

The T6 Adapters with AOC-SFP28-CABLE-10M cables enable a unified wire for LAN, SAN, and cluster traffic. Built upon a combination of high bandwidth and low latency architecture, the T6 solution offers a complete set of storage and cluster protocols operating over Ethernet. T6 solution's port-to-port and adapter-to-adapter failover features are ideal for critical applications that require redundancy and high-availability capabilities. Full Software suite was run with these cables and Chelsio recommends using these cables only with Chelsio Adapters to allow the Adapter warranty and support structure to remain intact.

Ordering Information

Model: AOC-SFP28-CABLE-10M (25 Gb/s 10m SFP28 to SFP28 Short Reach Active Optical Cable)

INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH CHELSIO PRODUCTS. NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. EXCEPT AS PROVIDED IN CHELSIO'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, CHELSIO ASSUMES NO LIABILITY WHATSOEVER, AND CHELSIO DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO SALE AND/OR USE OF CHELSIO PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. CHELSIO PRODUCTS ARE NOT INTENDED FOR USE IN MEDICAL, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS. CHELSIO MAY MAKE CHANGES TO SPECIFICATIONS AND PRODUCT DESCRIPTIONS AT ANY TIME WITHOUT NOTICE.

Copyright © 2018 - Chelsio Communications - All Rights Reserved.